



Generators combiner boxes

GAK 303-MC4 Junction box PV GAK DIS50VG-1000-6ST-3MPP MC4



Characteristics
Generator boxes with preassembled surge protection:

- Legend**
- a) type 1+2 GAK DIS 60 VGPVS-1000-6ST-3MPP
 - b) type 1+2 GAK DIS 50 PVS-1000-6ST-3MPP
 - c) type 1+2 GAK DIS 50 VGPVS-1000-6ST-3MPP
 - d) type 2 GAK DIS 50 PV-1000-6ST-3MPP

Article-Nr.	E-Number	 Typ/Type	 V U _C	 kA I _{imp}	 kA I _{max}	 ns t _A	 kV U _P	 mm ²		
296.050.503	969 112 384	T1 / T2	≤1200VDC	6.25	40	≤25	2.8	2.5 - 25	c)	1

Technical Specifications: Junction box PV GAK DIS50VG-1000-6ST-3MPP MC4 GAK 303-MC4

Article No.	296.050.503
SPD type	T1 / T2
Number of poles	2
max. discharge current (I _{max})	40 kA
Nominal line voltage U _n DC	1000 V
Impulse current [I _{imp}] (10/350)	6.25 kA
Discharge current max. (8/20) μ s [I _{max}]	60 kA
Voltage protection level [U _p]	2.8 kV
Operation voltage max. [U _c]	≤1200VDC
Operating current [I _c]	0 kA
Follow current [I _F]	0 kA
follow current extinguishing capability [I _{fi}]	Unendlich
Response time [t _a]	≤25
Short circuit resistance (I _{cw})	10 kA
Fault indication	Mechanisch, Rot
Temperature range	-40 - 85
Signaling on the device	Optic
Signaling contact	Yes
Connection cross section solid / stranded max.	1.5 mm ²
Switching capacity signaling contact	250 V / 0,5 A (AC) - 30 V / 2 A (DC)
Energetically coordinated protective effect to the terminal	Yes
System configuration DC	Yes
Construction size	3 modular spacing
Nominal discharge current [I _n]	15/Pol
Nominal cross section conductor	2.5 - 25
Integrated backup fuse	No
Exhausting	No
Mounting method	DIN rail (top hat rail) 35 mm
Degree of protection (IP)	IP20
Casing	
degree of protection	IP65
number of modules	28
contract rail	DIN-Schiene
String / MPP	6ST-3MPP
inputs PG / MC4	MC 4
outputs PG / MC4	MC 4
Switch	
Switching capacity voltage max. U _{oc} Max.	1000 V
Switching current max. I _{sc} Max.	30 A
Cross-sectional area	6 mm ²
Standards	
Test standards USA	UL 1449 ed.3
Test standards Europe	EN 50539-11
Test standards France	UTE C61-740-51
Homologation	VDE, ÖVE und UL
comment	
comment	c)
Commercial specification	
Customs number	85372000
country of origin	CH
Texte	
comment	c)