


Conductor connections and junctions

AV 80



Application
Riveted application for the following material thicknesses:
Inox 0.5 to 4.4 mm
TiZn 0.7 to 4.4 mm
Cu 0.6 to 4.4 mm
Al 2.0 to 4.4 mm
Note: riveted application is considered Class-H tested only in conjunction with AV81 rivets.
Screwed application for the following material thicknesses:
Inox 0.5 to 2.5 mm
TiZn 0.7 to 2.7 mm
Cu 0.6 to 2.6 mm
Al 0.8 to 2.8 mm

Characteristics
For connecting an bridging stuctural components.
Lightning surge current resistant class H (100kA9 according to EN 62561-1
Ends dip tinned with 6 rivet holes Ø 4.1mm / 1 hole M8
Length = center hole to center hole

Article-Nr.	E-Number									
275.063.006	156 943 860	H	CuvSn	400	30x2	8.2	35			5

Accessories										
 Multi-range blind rivets 275.063.011										
Article-Nr.	E-Number									
275.063.011	156 990 020	H	0.5 - 6.5	10	RAL 9006, silver	4.1			a)	70

Accessories										
 Hexagon head screw M8x16 951.04.339										
Article-Nr.	E-Number									
951.04.339		InoxA4	M8x16							1

Accessories										
 Hexagon Nut M8 950.04.300										
Article-Nr.	E-Number									
950.04.300		InoxA2	M8							500

Accessories



Washer A2 Ø 24/8.4x2 953.04.082

Article-Nr.	E-Number									
953.04.082		24	2	8.4	Inox A2					100



Technical Specifications: AV 80

Article No.	275.063.006
Approved class H / N (EN 62561-1)	H
Material	CuvSn
Nominal cross section conductor	35 mm²
Length a	400 mm
Band size	30x2
Eyelet diameter	8.2 mm
Shape of conductor	Flat
Insulated	No
Cable width approx.	30 mm
Cable height approx.	2 mm
Conductor category	Class 6 = very flexible
Braided	Yes
Connection lugs drilled	Yes
required torque	20 N·m
Commercial specification	
Customs number	74130000
country of origin	CE

