


Conductor connections and junctions

■ AV 26 Contact clip



**Characteristics**  
With connection terminal for longitudinal and transversal wiring.  
Not to be used in the ground.

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |  |
|-------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|--|-------------------------------------------------------------------------------------|
| 280.105.001 | 156 831 000 | H                                                                                 | InoxA2                                                                            | 6 - 10                                                                            | 20 - 40                                                                           |  |  |  |  | 10                                                                                  |

Technical Specifications: **Contact clip AV 26**

|                                            |             |
|--------------------------------------------|-------------|
| Article No.                                | 280.105.001 |
| Approved class H / N (EN 62561-1)          | H           |
| Material                                   | InoxA2      |
| Wire diameter                              | 6 - 10 mm   |
| External diameter                          | 20 - 40 mm  |
| Cross section of the connecting conductors | 25 - 50 mm² |
| Clamping/chucking range                    | 20 - 40 mm  |
| Number of conductors                       | 1           |
| Surface protection                         | unbehandelt |
| required torque                            | 15 N·m      |
| Commercial specification                   |             |
| Customs number                             | 85389000    |
| country of origin                          | CH          |
| Logistic specification                     |             |
| VPE Weight                                 | 1.515 kg    |

