


Conductor connections and junctions

■ AV 46 Cross connectors



Characteristics
Cross connector 20x3mm, suitable for parallel connections up to 30x3mm

Legend
a) 2-parts
b) 3-parts

Article-Nr.	E-Number									
275.045.404	156 831 530	H	ok	Cu	M6x20	6 - 8	20x3/30x3		a)	25
270.001.404	156 831 540	H		InoxA2	M6x20	6 - 8	20x3/30x3		a)	25
270.003.000	156 831 570			InoxA2	M6x25	6 - 8	20x3/30x3		b)	25

Technical Specifications: **Cross connectors AV 46**

	275.045.404	270.001.404	270.003.000
Approved class H / N (EN 62561-1)	H		
Suitable for use in soil	ok		
Material	Cu	InoxA2	
Screw	M6x20		M6x25
Wire diameter	6 - 8 mm		
Band size	20x3/30x3 mm		
Surface protection	unbehandelt		
Type of connector	T-/cross-/parallel connector		
Suitable for connection	Round conductor Rd 7-10 / flat conductor FI 30		
Type of fastening screws	Hexagon screw		
required torque	6 N·m		
Commercial specification			
Customs number	85389000		
country of origin	CH		
Logistic specification			
VPE Weight	2.204 kg	1.99 kg	2.812 kg

