

Loop with cotter

FRL 2 Loop with cotter



Application
For standard insulators and copper or bronze cables or wires

Characteristics
Conductor attachment via captive corded cotter made of stainless steel, loop on the side for opening

Material
Inox A2 body, copper sling

Article-Nr.	E-Number									
111.055.043	156 252 030	InoxA2	4 - 5	16						25
111.056.025	156 252 050	InoxA2	6 - 8	25 - 35						25
111.057.102	156 252 070	InoxA2		50						25

Technical Specifications: **Loop with cotter FRL 2**

	111.055.043	111.056.025	111.057.102
Material	InoxA2		
Nominal cross section conductor	16 mm²	25 - 35 mm²	50 mm²
Wire diameter	4 - 5 mm	6 - 8 mm	
For pull protected connections	Yes		
Suitable for round conductors	Yes		
Sleeve form	Short		
Suitable for high temperatures (to 650 °C)	No		
Oil stop/centre bar	No		
Suitable for fine strand conductors	No		
Type of connection	End connector		
Suitable for insulated varnish	No		
Insulation	None		
Surface protection	blank		
Useful for stranded conductors	Yes		
Voltage level	Up to 35kV		
Suitable for flat conductors	No		
Suitable for solid cores	Yes		No
Model	Standard version		
Number of branches	1		
Commercial specification			
Customs number	85359000		
country of origin	CH		
Logistic specification			
VPE Weight	4.248 kg	8.68 kg	9.265 kg

