

Ring earthing components

RE 36 Pipe clip



Characteristics

Turnbuckle M10x90
Incl. connection plate

Article-Nr.	E-Number									
260.003.074	156 832 480	ok	InoxA4	6 - 10	80	3"	94 - 100	M10x90		1
260.004.076	156 832 490	ok	InoxA4	6 - 10	100	4"	114 - 120	M10x90		1
260.005.077	156 832 500	ok	InoxA4	6 - 10	110	4 1/2"	124 - 130	M10x90		1
260.006.078	156 832 510	ok	InoxA4	6 - 10	125	5"	140 - 146	M10x90		1
260.007.079	156 832 530	ok	InoxA4	6 - 10	150	6"	166 - 172	M10x90		1
260.008.080	156 832 540	ok	InoxA4	6 - 10	175	7"	193 - 199	M10x90		1
260.009.081	156 832 550	ok	InoxA4	6 - 10	200	8"	219 - 225	M10x90		1
260.010.082	156 832 560	ok	InoxA4	6 - 10	250	10"	272 - 278	M10x90		1
260.011.083	156 832 570	ok	InoxA4	6 - 10	300	12"	323 - 329	M10x90		1
260.012.084	156 832 580	ok	InoxA4	6 - 10	350	14"	374 - 380	M10x90		1
260.012.086	156 831 190	ok	InoxA4	6 - 10	400	16"	429 - 435	M10x90		1

Technical Specifications: Pipe clip RE 36

	260.003.074	260.004.076	260.005.077	260.006.078
Suitable for use in soil	ok			
Material	InoxA4			
Wire diameter	6 - 10 mm			
Nominal width	80	100	110	125
Nominal width	3" Zoll	4" Zoll	4 1/2" Zoll	5" Zoll
Clamping range pipe diameter	94 - 100 mm	114 - 120 mm	124 - 130 mm	140 - 146 mm
Cross section of the connecting conductors	50 mm ²			
Number of conductors	1			
Surface protection	unbehandelt			
Screw	M10x90			
Clamping/chucking range	90 - 94 mm	113 - 117 mm	125 - 129 mm	142 - 146 mm
required torque	25 N·m			
Commercial specification				
Customs number	85389000			
country of origin	CH			
Logistic specification				
VPE Weight	0.632 kg	0.66 kg	0.676 kg	0.7 kg

	260.007.079	260.008.080	260.009.081	260.010.082
Suitable for use in soil	ok			
Material	InoxA4			
Wire diameter	6 - 10 mm			
Nominal width	150	175	200	250
Nominal width	6" Zoll	7" Zoll	8" Zoll	10" Zoll
Clamping range pipe diameter	166 - 172 mm	193 - 199 mm	219 - 225 mm	272 - 278 mm
Cross section of the connecting conductors	50 mm ²			
Number of conductors	1			
Surface protection	unbehandelt			
Screw	M10x90			
Clamping/chucking range	165 - 169 mm	193 - 197 mm	220 - 224 mm	272 - 276 mm
required torque	25 N·m			
Commercial specification				
Customs number	85389000			
country of origin	CH			
Logistic specification				
VPE Weight	0.74 kg	0.774 kg	0.82 kg	0.89 kg

	260.011.083	260.012.084	260.012.086
Suitable for use in soil	ok		
Material	InoxA4		
Wire diameter	6 - 10 mm		
Nominal width	300	350	400
Nominal width	12" Zoll	14" Zoll	16" Zoll
Clamping range pipe diameter	323 - 329 mm	374 - 380 mm	429 - 435 mm
Cross section of the connecting conductors	50 mm ²		
Number of conductors	1		
Surface protection	unbehandelt		
Screw	M10x90		
Clamping/chucking range	320 - 324 mm	371 - 375 mm	427 - 431 mm
required torque	25 N·m		
Commercial specification			
Customs number	85389000		
country of origin	CH		
Logistic specification			
VPE Weight	0.976 kg	1.053 kg	1.136 kg

